

# TÜNKERS



**New Development**

## Packaging System „FAS 480“ for folded cartons

suitable for combination with Carton Gluers comprising of:

- one guide bar to control the carton stream of cartons coming from the Gluer
- one speed sensor, which ensures that the system runs in synchronisation with the Gluer
- one erection including belts, spring loaded and adjustable reversing rollers, as well as guides for the erection of the flat cartons
- one reversing head section, by means of which the erected stream of cartons is transported at 90 degrees into the cross transport section, whilst remaining the pre-selected counting in the Gluer
- one cross transport section with side guides as well as driven transport belts and a end stop, which moves along with stream of carton as they arrive
- one drive and control cabinet including electrical in-machine installation for 220 Volt, A.C., 50 Hz.





## Technical Details

1. Carton materials	Board E-flute B-flute
2. Carton Types	Straight-line cartons 4 Point Cartons 6 Point Cartons      Lockbottom cartons
3. Carton Sizes	Width: min. 40 mm Width: max. 420 mm  Length: min. 40 mm Length: max. 480 mm
max. thickness of shingled carton stream:	50 mm
<b>Power Supply:</b>	1 KVA
<b>Weight:</b>	net about 450 kg

## Optional Lifting Table

As an option for the **FAS 480** we offer a pneumatically controlled lifting table, which makes packing of the cartons into the outer box much easier. The lifting table consists of a height adjustable steel pipe frame with Formica covered table, of which a section is tilted by 35 degrees and can be raised level by means of a foot switch. (5.5 bar)

**The complete system is movable on wheels and can be supplied as a left-handed or right-handed Model.**

# TÜNKERS



TÜNKERS Maschinenbau GmbH  
Am Rosenkoth 8 · 40880 Ratingen  
Postfach 1716 · 40837 Ratingen  
Tel. 0 2102/4517-0 · Telex 8 585 176 · Fax 0 2102/44 58 08